

HITACHI
Inspire the Next

Performa™ CP-RS55



- 1,500 ANSI lumens
- Native SVGA resolution
- 4.84 lbs
- RGB / Composite / S-video inputs
- Digital gamma correction
- HDTV theater ready
- FCC Class B
- 16:9 mode
- Vertical keystone correction
- Reverse image function for ceiling mount
- Remote control
- My Memory
- Whisper mode 32dB
- Progressive scan
- Digital zoom (x4)
- Freeze function
- Fixed zoom & manual focus
- Kensington security slot
- My Screen

SPECIFICATIONS

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

| | | | |
|--------------------------------|---|--|------------------------------|
| Model name | CP-RS55 | | |
| Liquid crystal panel structure | 0.55" polysilicon active-matrix TFT x 3 | | |
| Number of pixels | 480,000 pixels | | |
| Resolution | 800 X 600 pixels | | |
| Colors | 16.7 million colors | | |
| Aspect ratio | Native 4:3/16:9 compatible | | |
| Lens | F1.65 (fixed), manual focus | | |
| Throw ratio (distance:width) | 1.8: 1 | | |
| Lamp | 165W UHB | | |
| Brightness | 1,500 ANSI lumens | | |
| Expected lamp life | Approx. 2,000 hours | | |
| Contrast ratio | 300 : 1 | | |
| Speakers | 1W x 1 | | |
| Power supply | AC100-120V/AC220-240V 50/60Hz | | |
| Power consumption | 240W | | |
| Operating temperature | 32°F ~ 95°F | | |
| Input signals | RGB | VGA, SVGA, XGA/SXGA (Compressed), MAC13', MAC16' | |
| | Composite video | NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60 | |
| | Component video | 480i, 575i, 480p, 1,080i, 720p | |
| Acoustic noise level | 38dB (32dB in whisper mode) | | |
| H sync | 15kHz ~ 91kHz | | |
| V sync | 50Hz ~ 120Hz | | |
| Vertical keystone correction | Digital keystone +/- 15° | | |
| Approvals | UL, C-UL, FCC Class B, CE, TUV | | |
| Input/Output terminals | RGB input | Analog RGB | 15-pin D-sub connector x 1 |
| | Video input | S-video | Mini DIN 4-pin connector x 1 |
| | | Composite video | RCA jack x 1 |
| | Audio | Input | Stereo mini jack x 1 |
| Control terminals | 9-pin D-sub connector x 1 (RS-232C control) | | |
| Chassis | Dimensions | 11.22" x 2.87" x 7.94" (W x H x D) | |
| | Weight | 4.84 lbs. | |
| | Supplied accessories | Remote Control, Batteries (AA), RGB Cable, Power Cord, Safety Instruction, Quick Start Guide, Users Manual CD-ROM, Lens Cap, Strap, Filter Cover | |
| Replacement parts | Lamp | CPRS55LAMP | |
| | Remote Control | (Part #: HL02151) | |



| Screen Size 4.3 | | Throw distance |
|-----------------|--------|----------------|
| Diagonal* | Width* | |
| 40 | 32 | 57 |
| 60 | 48 | 87 |
| 80 | 64 | 116 |
| 100 | 80 | 145 |
| 120 | 96 | 174 |
| 150 | 120 | 218 |
| 200 | 160 | 291 |

Throw ratio: 1.8:1 (distance:width)

*: Measured in inches

PERFORMA™
CP-RS55 Dimensions
(Incl. protruding part)

