

# CP-X3010Z Features & Benefits

**HITACHI**  
Inspire the Next

 Closed Captioning

**Touchboards**

205 Westwood Ave, Long Branch, NJ 07740  
Phone: 866-94 BOARDS (26273) / (732)-222-1511  
Fax: (732)-222-7088 | E-mail: sales@touchboards.com



## Key Features

3,000 Lumens	Bright and clear images in any class room or conference room.
Hybrid Filter (5,000 Hours Between Maintenance)	The Hitachi CP-X3010Z projector provides users with a lower total cost of ownership by offering less frequent maintenance.
Lamp Life Approximately 6,000 Hours (Eco Mode)*	Another key to low total cost of ownership is a long life lamp. The CP-X3010Z lamp is rated at 3,000 hours in standard mode and 6,000 hours in eco mode.
16 watt Audio Output	16W audio output eliminates the need to connect external speakers.
Audio Pass Through	The projector can output audio in stand-by mode, allowing you to listen to external speakers via the projector's audio output. Keeping the projector in standby mode saves lamp life.
2 RGB in / 1 RGB out / Component/Composite/S-Video	The rich connectivity allows you to connect to two computer and multiple video sources at the same time. Monitor loop-through for ease of use with desktop computers.
Power Saving Mode	The Saving mode reduces the stand-by power consumption to less than 1W with limitation of some features.
Lamp door on Top	Easy maintenance is another attractive function of the CP-X3010Z, as its lamp door is on top of the model.
Template Function	Line templates in the projector menu can help when writing on a whiteboard. There are four types of line templates to choose from. <b>Exclusive to Hitachi.</b>
Transition Detector	A security sensor located inside the projector recognizes when the projector has been moved. Moving the projector with out using the correct PIN Code will disable the projector. <b>Exclusive to Hitachi.</b>
White Board Mode	Limits the peak white by changing the gamma curve limiting its brightness when used with a whiteboard to protect the eye health of teachers and students. <b>Exclusive to Hitachi.</b>
Input Source Naming	Users can name input sources in simple language instead of factory default name. <b>Exclusive to Hitachi.</b>
IR remote Frequency Change	To avoid conflict with fluorescent lights or IrDA (IR signal) from notebook PC, the frequency of the IR remote control can be changed from the menu. <b>Exclusive to Hitachi.</b>
My Button / My Source (Doc Camera)	Two customizable buttons on the remote control allow users to create a shortcut for any projector command such as: Direct Input (RGB1, S-video etc.), Picture Mode, or Filter Reset. For connection to a document camera, My Source allows users to add a third "Document Camera" source button.
PIN Lock/ My Screen PIN Lock/ My Text	PIN lock protection can limit projector users. My Screen PIN Lock keeps captured images on the startup screen. Users can set a school's name or company's logo to "My Screen" clearly identifying ownership My Text provides the ability to write text on the start up screen. Example, model name, serial number, or location.
Auto V Keystone	Automatic Vertical Keystone detects the angle of the Projector and corrects the image.
Serial Number Label on Side	It is convenient for users or auditors to be able to check the model name and serial number of an asset easily when the product is ceiling mounted. The label is upside-down and easily viewable for ceiling-use.
Closed Captioning	CC1, CC2, CC3, CC4

\* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.